Pro Sweep[™] 5200





Say goodbye to cores.

Pro Sweep 5200

- 132 cm (52") sweeping width
- Ground-following design
- Tow behind and offset collection positions
- .71 cu. metres (25 cu. ft.) hopper
- High-lift dump system

Aeration cores and other turf debris need to go somewhere. And that somewhere is the hopper of a Toro® Pro Sweep™ 5200. Faster and more effective than traditional methods of collecting cores and debris, the 5200 sweeps greens, sports fields or any turf clean. If you're looking to bring efficiency into your turf sweeping process, and return to play sooner, invest in a Toro Pro Sweep 5200.



Count on Innovation

A clean sweep.

The Pro Sweep works remarkably well on undulating terrain. That's the result of a floating sweeper head that pivots sideto-side and a sub frame that pivots front-to-back. Together they allow the sweeper to accurately follow contours on uneven terrain.





More time to play.

The Pro Sweep saves time and labour costs while getting your field or golf course back into play faster. By sweeping up cores almost as fast as you pull them, turf can be topdressed and ready for play in no time. The offset collection position keeps the tow vehicle from running over cores before they reach the sweeper. In addition, the windrow kit pushes cores away from the Pro Sweep's tyre so you won't crush them. The hopper holds enough cores to sweep most greens and features a high-lift dump so you only need to handle material once. An innovative adjustment system allows for fast, precise brush height adjustment to accommodate a variety of turf conditions.



The standard control box mounts in the operator area of your Workman.





Add the optional electric offset to shift between the transport position and the collect position without stopping.

Accessories

Windrow kit



Tyre scrapers





Specifications for Pro Sweep™ 5200

Power & Towing Requirements

Utility vehicle: 30.3 l/min (8 GPM) @ 2000 psi

Tractor: 18.6 kW (25 hp) minimum

Hitch: 19 mm (3/4") hitch pin with safety linchpin

(Workman® vehicles require the heavy-duty draw bar and high-flow

hydraulics kit.)

Collection System

Type: Hydraulic-powered rotary brush *Sweeping width:* 132 cm (52")

Roller: 152 mm (6") diameter, full-width, adjustable

Ground following: Floating brush housing

Collect position: Tow directly behind or offset to the side of the

vehicle, optional electric tongue offset kit

Traction: Pivoting sub frame allows for positive tongue weight

Hopper

Capacity: .71 cu. metres (25 cu. ft.)

Lift: Hydraulic powered lift cylinder, high-lift

Operating Speed

Forward sweeping: 0-6.4 km/h (0-4 mph), infinitely variable Forward transport: 0-24 km/h (0-15 mph)

Dimensions & Weight

Height: 173 cm (68") Length: 368 cm (145") Width: 221 cm (87")

Dump height clearance: 173 cm (68") Weight: 686 kgs (1,512 lbs.) empty

Tyres: 26.5 x 14-12

Options

Electric offset, windrow kit, brake kit, tyre scrapers, jack stand

Warranty: Two-year, comprehensive

TORO® PROFESSIONAL SERVICES

Toro Financing Many flexible financing options are available to meet your specific operational requirements.

Toro Genuine Parts Keep the productivity and performance of your equipment at its peak by using genuine Toro replacement parts. Find and identify your replacement parts online at www.Toro.com/partsviewer.

Toro Training Toro Technical Service Schools are available from your local distributor. Explore the training and customer care areas of Toro.com and ToroNSN.com for readily available on-line education and training materials.

Toro Controller Repair Provides irrigation controller boards ready for immediate board exchange to assure that downtime is minimal and your turf stays protected. Toro is the choice for reliability. +1909 785 3630

Toro NSN® An industry-first support network that provides reliable, around-the-clock irrigation central control system trouble-shooting and operation assistance. For assistance please contact:

Canada / Mexico / Latin America +1325 673 8762 Europe / Middle East / Africa +32 14 56 29 33 Australia / Asia-Pacific +61 7 3268 2154



