



# Introducing the bold new Toro Z Master<sup>®</sup> and GrandStand<sup>®</sup> Revolution Series commercial mowers.

Developed by Toro, industry-leading HyperCell® batteries deliver superior power that devours the lushest of lawns all day long...without bogging down! Built on the same proven GrandStand® and Z Master® chassis and TURBO FORCE® deck that you've trusted for years, the new Revolution Series delivers lower overall cost over the machine's lifetime.

### PATENT-PENDING SOFTWARE CONTROLS

To optimise machine feel and response, including speed control

## HYPERCELL® LITHIUM ION BATTERY ALL-DAY RUNTIME

Toro designed to operate with machinery and meet landscaper needs

#### **DECK RAKE ADJUSTMENT**

To optimise runtime and quality of cut



### toro.com.au

Customer Service 1800 356 372

©2023 The Toro Company. All Rights Reserved. 06-2023

	GRANDSTAND*		Z MASTER' MyRIDE' SUSPENSION SYSTEM						
	1885	50TE	1874	OTE	187	50TE	187	65TE	
POWER SYSTEM					:		:		
Battery	HyperCell"		HyperCell°		HyperCell*		HyperCell*		
Battery Quantity	8		10		10		10		
Battery Capacity	18.4 kWh		23.4 kWh		23.4 kWh		23.4 kWh		
tuntime (hrs)	4 - 7+		4 - 7+		4 - 7+		4 - 7+		
Charge Time (hrs)	12		8		8		8		
Charge Type	1.2 kW		3.3kW 240V Standard		3.3kW 240V Standard		3.3kW 240V Standard		
RACTION									
Transmission	Planetar	Planetary Gearset		y Gearset	Planetary Gearset		Planetar	y Gearset	
Motors	Commercial High Torque								
MOWING DECKS		9		9 4-2					
leck Size	52" (13	2.1 cm)	/A8" (12	1.9 cm)	52"	(132.1 cm)	An" (1	152.4 cm)	
Cutting Deck	7-Gauge TURBO FORCE®		7-Gauge TURBO FORCE®		7-Gauge TURBO FORCE®		7-Gauge TURBO FORCE		
-	7-Gauge TORBO FORCE Side		Side		7-Gauge TORBO FORCE Side		7-Gauge TORBO FORCE Side		
Jeck Discharge	5.5" (14 cm)								
Deck Depth	5.5" (14 cm) 9" (22.9 cm) Diameter								
Spindle Housings	Cast Aluminum w/ Blade Retainer								
Cutting Height	1.5" - 5.0" in .25" increments (3.8 – 12.7 cm in 0.6 cm increments)		1.5" - 5.0" in .25" increments (3.8 – 12.7 cm in 0.6 cm increments)		1.5" - 5.0" in .25" increments (3.8 – 12.7 cm in 0.6 cm increments)		1.5" - 5.0" in .25" increments (3.8 – 12.7 cm in 0.6 cm increments)		
Blades	.204" (0.5 cm) Heat-Treated Steel								
Blade Tip Speed	Adjustable		Adjustable		Adjustable		Adjustable		
Electric Deck Lift	N/A		Optional		Optional		Optional		
Motors	Mid-Mount Commercial High Torque								
Rake Adjustment	Yes		Yes		Yes		Yes		
FEATURES					:	100			
MyRIDE' Suspension System	N	/Δ	Stan	dard	Sta	ındard	Star	ndard	
	N/A		Standard Deluxe Comfort		Deluxe Comfort		Standard Deluxe Comfort		
Operator Seat	N/A		w/Armrests		w/Armrests		w/Armrests		
Max Traction Unit Speed advertised)	10 mph (16.1 km/h)		12 mph (19.3 km/h)		12 mph (19.3 km/h)		12 mph (19.3 km/h)		
Max Traction Speed Control	Yes - 7 speed settings								
Orive Tyres	Super Turf 20" x 10" x 10"		Super Turf 24" x 9.5" x 12"		Super Turf 24" x 12" x 12"		Super Turf 24" x 12" x 12"		
	(50.8 x 25.4 – 25.4 cm)		(61 x 24.1 – 30.5 cm)		(61 x 30.5 – 30.5 cm) Black Steel		(61 x 30.5 – 30.5 cm) Black Steel		
Orive Wheels	Black Steel 11" x 4" - 5" Flat-Free		Black Steel 13" x 6.5" - 6" Flat-Free		13" x 6.5" - 6" Flat-Free		Black Steel 13" x 6.5" - 6" Flat-Free		
Front Caster Tyres	Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)		Semi-Pneumatic (33 x 16.5 – 15.2 cm)		Semi-Pneumatic (33 x 16.5 – 15.2 cm)		Semi-Pneumatic (33 x 16.5 – 15.2 cm)		
Technology		Hour Meter, USB Included							
ROPS Profile / PIN Type	N	N/A		Square Tube / Pin w/Lanyard		Square Tube / Pin w/Lanyard		Square Tube / Pin w/Lanyard	
Knee Pad	Deluxe	Deluxe Durable		N/A		N/A		N/A	
Operator Platform	Foldable w/Bumper Cushions		N/A		N/A		N/A		
_ED Lights	Standard		Standard		Standard		Standard		
Parking Brake	Integrated in	Integrated in Transmission Automatic		Integrated in Transmission Automatic		Integrated in Transmission Automatic		Integrated in Transmission Automatic	
Mower Warranty*	5-Year/12	5-Year/1200-Hour^ First 2-Year No Hour Limit		5-Year/1500-Hour^ First 2-Year No Hour Limit		5-Year/1500-Hour^ First 2-Year No Hour Limit		5-Year/1500-Hour^ First 2-Year No Hour Limit	
WEIGHTS AND MEASUREM			7.1002.10011				7.1.512.1041		
Veight	1,109 lbs.	503.0 kg	1,354 lbs.	614.2 kg	1,381 lbs.	626.4 kg	1,461 lbs.	662.7 kg	
ROPS Height (Folded)	N/A	N/A	46.3"	117.6 cm	46.7"	118.6 cm	49.9"	126.7 cm	
ROPS Height (Upright)	N/A	N/A	71.6"	181.9 cm	72.1"	183.1 cm	72.1"	183.1 cm	
Deck Clearance Width	53.8"	136.7 cm	52.2"	132.6 cm	60.4"	153.4 cm	60.4"	153.4 cm	
Deflector Width	67.8"	172.2 cm	63.1"	160.3 cm	75.2"	191.0 cm	75.2"	191.0 cm	
Length (Platform Up)	61.0"	154.9 cm	N/A	N/A	N/A	N/A	N/A	N/A	
Length	75.8"	192.5 cm	81.6"	207.3 cm	81.6"	207.3 cm	81.6"	207.3 cm	

<sup>&</sup>quot;Warranty does not include battery. See your local Toro dealer or refer to owners manual for complete warranty details. "Whichever occurs first.